



Integrated Smart Agricultural Field Protection and Automatic Irrigation System

M. Nirmala Devi, C. Nishanthi, A. Savitha, P. Vinitha

Gnanamani College of Technology, Namakkal, Tamil Nadu, India

Publication History: Received: 25.02.2026; Revised: 20.03.2026; Accepted: 25.03.2026; Published: 28.03.2026.

ABSTRACT: This paper presents an integrated smart agricultural field protection and automatic irrigation system using advanced Internet of Things (IoT) technology. The proposed system is designed to monitor environmental conditions such as soil moisture, temperature, and humidity in real-time. The collected data is processed using a NodeMCU microcontroller and transmitted to a Raspberry Pi for intelligent decision-making. Based on soil moisture levels, the system automatically controls irrigation using a relay-driven water pump, thereby reducing water wastage and improving efficiency.

In addition to irrigation, the system incorporates a field protection mechanism using an ESP32 camera module, which continuously monitors the agricultural field for any intrusion or unwanted activities. A GSM module is integrated to send real-time alerts to farmers, ensuring quick response and improved crop safety. Furthermore, the system includes an intelligent animal detection mechanism. When an animal enters the field, the system analyses the type of animal and generates a specific irritating sound to repel it.

To prevent animals from getting habituated to a particular sound, the system is programmed to automatically change the sound at regular intervals. For each type of animal, multiple irritating sounds are stored, and the system cycles through these sounds every five days. This dynamic sound variation ensures continuous effectiveness of the deterrent mechanism and enhances field protection.

The proposed system minimizes manual labor, optimizes water usage, and improves overall agricultural productivity. It is cost-effective, reliable, and suitable for modern smart farming applications.

KEYWORDS: Smart Agriculture, IoT, Automatic Irrigation System, Field Protection, Animal Detection, ESP32 Camera, Raspberry Pi, Soil Moisture Sensor, GSM Module, Sound Deterrent System, Dynamic Sound Variation

I. INTRODUCTION

Agriculture plays a crucial role in the economic development of a country, especially in developing nations like India where a large portion of the population depends on farming for their livelihood. However, traditional farming methods often involve manual irrigation practices, lack of real-time monitoring, and inefficient use of water resources. These challenges lead to reduced productivity and increased labour effort. Additionally, crop damage caused by animals entering agricultural fields remains a significant problem faced by farmers.

In recent years, the advancement of technologies such as the Internet of Things (IoT), embedded systems, and automation has opened new opportunities for modernizing agriculture. Smart agriculture aims to enhance productivity by using sensors, intelligent monitoring systems, and automated control mechanisms. Among these, automated irrigation systems based on soil moisture levels have gained importance due to their ability to optimize water usage and improve crop yield.

This paper presents an integrated smart agricultural system that combines automatic irrigation with intelligent field protection. The system continuously monitors soil moisture, temperature, and humidity using sensors connected to a NodeMCU microcontroller. Based on the collected data, irrigation is automatically controlled using a relay and water pump, ensuring that crops receive the required amount of water without wastage.

In addition to irrigation, the proposed system incorporates a real-time monitoring mechanism using an ESP32 camera module and a Raspberry Pi for advanced processing. The system is capable of detecting animals entering the field and



analysing their presence. Upon detection, a specific irritating sound is generated using a speaker system to repel the animal effectively.

A key innovation of this system is the implementation of a dynamic sound deterrent mechanism. Instead of using a single repetitive sound, the system stores multiple sound patterns for each type of animal. These sounds are automatically changed at regular intervals of five days. This prevents animals from becoming habituated to a particular sound, thereby maintaining the effectiveness of the deterrent system over time.

Furthermore, a GSM module is integrated to provide real-time alerts to farmers whenever intrusion or abnormal conditions are detected. This enables quick action and enhances field security. The overall system is designed to be cost-effective, reliable, and easy to implement in real-world agricultural environments.

Thus, the proposed system addresses major challenges in agriculture such as water management, crop protection, and labour reduction by providing an efficient and intelligent solution for modern smart farming.

II. LITERATURE REVIEW

In recent years, significant research has been carried out in the field of smart agriculture using Internet of Things (IoT) technologies. Many researchers have focused on developing automated irrigation systems that utilize soil moisture sensors to monitor soil conditions and control water supply efficiently. These systems have proven to reduce water wastage and improve crop yield by ensuring optimal irrigation.

Several studies have proposed the use of wireless sensor networks (WSN) for real-time monitoring of environmental parameters such as temperature, humidity, and soil moisture. These systems enable farmers to remotely monitor their fields and make informed decisions. The integration of microcontrollers such as Arduino and NodeMCU has further enhanced the efficiency and affordability of such systems.

In addition to irrigation, field monitoring and security have also gained attention. Camera-based monitoring systems using modules such as ESP32 have been implemented to detect motion and capture real-time images of agricultural fields. These systems help in identifying intrusions and provide visual data for analysis. Some approaches also include the use of image processing techniques for detecting animals and preventing crop damage.

Various methods have been proposed for animal deterrence, including the use of light, alarms, and basic sound systems. However, these conventional methods are often ineffective as animals tend to become habituated to repetitive signals over time. As a result, the efficiency of such systems decreases significantly after prolonged use.

Recent advancements have explored intelligent deterrent systems that use adaptive techniques to improve effectiveness. However, many existing solutions lack dynamic adaptability and do not consider behavioural patterns of animals. This creates a need for a more advanced and reliable system that can continuously adapt and respond to changing conditions.

The proposed system addresses these limitations by integrating an intelligent animal detection mechanism with a dynamic sound deterrent system. By storing multiple sound patterns for different animals and automatically changing them at regular intervals, the system ensures long-term effectiveness. This innovative approach enhances field protection while maintaining the benefits of automated irrigation and real-time monitoring.

Thus, the proposed work combines the strengths of existing technologies while overcoming their limitations, making it a comprehensive solution for modern smart agriculture.

III. RESEARCH METHODOLOGY

The proposed system integrates multiple hardware and software components to achieve efficient irrigation and intelligent field protection. The system primarily consists of soil moisture sensors, temperature and humidity sensors, NodeMCU microcontroller, Raspberry Pi, ESP32 camera module, GSM module, relay module, speaker system, and a water pump.

Initially, the soil moisture sensor continuously monitors the moisture content present in the soil. The sensed data is transmitted to the NodeMCU microcontroller, which acts as the primary control unit. Along with soil moisture,



environmental parameters such as temperature and humidity are also recorded to provide better decision-making conditions.

The NodeMCU processes the incoming data and sends it to the Raspberry Pi for advanced analysis. The system is programmed with predefined threshold values for soil moisture. When the moisture level drops below the threshold, the NodeMCU activates the relay module, which in turn switches on the water pump to irrigate the field. Once the required moisture level is achieved, the system automatically turns off the pump, ensuring efficient water utilization.

For field protection, the ESP32 camera module continuously monitors the agricultural field. When motion is detected, the system captures real-time images and sends them to the Raspberry Pi for processing. The Raspberry Pi analyzes the captured data to identify the presence and type of animal entering the field.

Based on the detected animal, the system selects a specific irritating sound from a predefined database. A speaker system is used to play the selected sound, which helps in repelling the animal without causing harm. Each animal category is associated with multiple sound patterns to improve effectiveness.

To further enhance the deterrent mechanism, the system is programmed to automatically change the sound at regular intervals of five days. This dynamic sound variation prevents animals from becoming habituated to a particular sound, thereby maintaining the efficiency of the system over long-term usage.

Additionally, the GSM module is integrated to send alert messages to the farmer whenever an intrusion is detected or when abnormal conditions occur. This allows the farmer to take immediate action if required.

The entire system operates in an automated manner, reducing human intervention while improving efficiency, crop safety, and resource management.

IV. RESULTS AND DISCUSSION

The implemented integrated smart agricultural system was tested under various environmental conditions to thoroughly evaluate its performance, reliability, and practicality in real-time agricultural scenarios. The soil moisture sensor continuously monitored the soil water content and accurately measured moisture levels, triggering the irrigation system whenever the soil moisture dropped below the optimal threshold. This automated operation resulted in efficient water usage, significantly reducing wastage compared to traditional manual irrigation methods, and ensuring that crops always received the appropriate amount of water.

The automatic irrigation system maintained optimal soil conditions across the field, which contributed to enhanced crop growth, improved productivity, and healthier plant development. The system operated entirely without manual intervention, thereby reducing labour requirements and allowing farmers to focus on other essential tasks.

The field monitoring subsystem, utilizing the ESP32 camera module, successfully detected motion within the agricultural area and captured real-time images of potential intrusions. The Raspberry Pi processed the captured images effectively, accurately identifying the presence of animals entering the field. This visual monitoring system not only ensured timely detection but also provided documented evidence for further analysis and preventive measures.

The animal deterrent system functioned efficiently by producing specific sound patterns tailored to repel different types of animals. By employing multiple sound variations and dynamically changing the sounds every five days, the system prevented animals from becoming accustomed to a single deterrent, thereby ensuring continuous and effective protection of the crops over time. The integration of the deterrent system with the monitoring subsystem created a proactive mechanism to safeguard the field from damage.

Additionally, the GSM module delivered timely alerts directly to the farmer's mobile device, enabling a rapid response to critical situations such as unauthorized intrusion or unexpected changes in soil conditions. This real-time notification feature enhanced the system's reliability and provided peace of mind to the user.

Overall, the proposed integrated smart agricultural system demonstrated high performance in terms of water management, crop protection, and automation efficiency. The results confirmed that the system is highly suitable for practical deployment in agricultural fields, offering a reliable, cost-effective, and scalable solution for modern farming practices.

Furthermore, the system’s modular design allows for future expansion, such as the addition of new sensors or integration with IoT platforms for more advanced data analytics and remote monitoring.



FIG: 1

V. CONCLUSION

The developed integrated smart agricultural field protection and automatic irrigation system offers an effective and practical solution to several critical challenges faced in modern agriculture. By combining IoT-based real-time monitoring with automated irrigation, the system ensures optimal water utilization, thereby minimizing wastage and contributing to sustainable farming practices. The automated irrigation mechanism maintains ideal soil moisture levels, which supports enhanced crop growth and productivity while reducing the dependency on manual labour.

In addition to water management, the intelligent animal detection system coupled with a dynamic sound deterrent mechanism significantly improves field security and prevents crop damage. The innovative approach of periodically changing sound patterns ensures the long-term effectiveness of the deterrent system, preventing animals from becoming accustomed to a single sound and maintaining continuous protection of the crops.

The system also provides real-time monitoring and control through the integration of sensors, microcontrollers, and GSM-based alert systems, enabling farmers to respond promptly to any critical situations. Its cost-effective design, modularity, and reliability make it suitable for practical implementation in agricultural fields, allowing easy scalability and potential future enhancements.



Overall, the designed system demonstrates a significant contribution toward the advancement of smart farming solutions, promoting both efficiency and sustainability in agriculture. The integration of automation, real-time monitoring, and intelligent deterrent mechanisms presents a comprehensive approach for modern agricultural practices, ensuring improved productivity, reduced labour, and effective crop protection.

VI. FUTURE WORK

1. Integration of artificial intelligence (AI) and machine learning (ML) for more accurate animal detection and classification.
2. Improvement of real-time image processing techniques for higher precision and a wider range of animals.
3. Implementation of adaptive sound generation based on animal behaviour for increased deterrent effectiveness.
4. Addition of cloud integration and mobile app support for remote monitoring and control.
5. Utilization of renewable energy sources such as solar power to enhance energy efficiency.
6. Incorporation of additional sensors to monitor soil nutrients and crop health for improved decision-making.

REFERENCES

1. S. Md. Jakheer, G. Ramesh, V. S. Kumar, et al., "Smart Agriculture System for Animal Detection and Automated Irrigation Control Using IR Camera, Raspberry Pi and Sensor Integration," *Int. J. Sci. Res. Eng. Manag.*, Apr. 2024. [Online]. Available: <https://www.researchgate.net/publication/379991186>
2. H. Narula and A. Pathak, "IoT Based Smart Agriculture and Animal Detection System," *Int. J. Res. Anal. Rev.*, 2022. [Online]. Available: <https://www.ijraset.com/research-paper/iot-based-smart-agriculture-and-animal-detection-system>
3. J. Miao, D. R. Rajasekhar, S. Mishra, et al., "A Fog-based Smart Agriculture System to Detect Animal Intrusion," *IEEE ICPADS*, 2023. [Online]. Available: <https://www.mdpi.com/1999-5903/16/8/296>
4. D. Vallejo-Gómez, M. Osorio, and C. A. Hincapié, "Smart Irrigation Systems in Agriculture: A Systematic Review," *Agronomy*, vol. 13, no. 2, 2023. [Online]. Available: <https://www.mdpi.com/2073-4395/13/2/342>
5. X. Liu, Z. Zhao, and A. Rezaeipannah, "Intelligent and automatic irrigation system based on IoT using fuzzy control technology," *Scientific Reports*, vol. 15, Art. no. 14577, 2025. [Online]. Available: <https://www.nature.com/articles/s41598-025-98137-2>
6. C.Nagarajan and M.Madheswaran - 'Stability Analysis of Series Parallel Resonant Converter with Fuzzy Logic Controller Using State Space Techniques'- Taylor & Francis, *Electric Power Components and Systems*, Vol.39 (8), pp.780-793, May 2011. DOI: 10.1080/15325008.2010.541746
7. C.Nagarajan and M.Madheswaran - 'Experimental verification and stability state space analysis of CLL-T Series Parallel Resonant Converter' - *Journal of Electrical Engineering*, Vol.63 (6), pp.365-372, Dec.2012. DOI: 10.2478/v10187-012-0054-2
8. C.Nagarajan and M.Madheswaran - 'Performance Analysis of LCL-T Resonant Converter with Fuzzy/PID Using State Space Analysis'- Springer, *Electrical Engineering*, Vol.93 (3), pp.167-178, September 2011. DOI 10.1007/s00202-011-0203-9
9. S.Tamilselvi, R.Prakash, C.Nagarajan, "Solar System Integrated Smart Grid Utilizing Hybrid Coot-Genetic Algorithm Optimized ANN Controller" *Iranian Journal Of Science And Technology-Transactions Of Electrical Engineering*, DOI10.1007/s40998-025-00917-z,2025
10. S.Tamilselvi, R.Prakash, C.Nagarajan, " Adaptive sliding mode control of multilevel grid-connected inverters using reinforcement learning for enhanced LVRT performance" *Electric Power Systems Research* 253 (2026) 112428, doi.org/10.1016/j.epsr.2025.112428
11. S.Thirunavukkarasu, C. Nagarajan, 2024, "Performance Investigation on OCF and SCF study in BLDC machine using FTANN Controller," *Journal of Electrical Engineering And Technology*, Volume 20, pages 2675–2688, (2025), doi.org/10.1007/s42835-024-02126-w
12. C. Nagarajan, M.Madheswaran and D.Ramasubramanian- 'Development of DSP based Robust Control Method for General Resonant Converter Topologies using Transfer Function Model'- *Acta Electrotechnica et Informatica Journal* , Vol.13 (2), pp.18-31, April-June.2013, DOI: 10.2478/aeeci-2013-0025.
13. C.Nagarajan and M.Madheswaran - 'DSP Based Fuzzy Controller for Series Parallel Resonant converter'- *Springer, Frontiers of Electrical and Electronic Engineering*, Vol. 7(4), pp. 438-446, Dec.12. DOI 10.1007/s11460-012-0212-0.
14. C.Nagarajan and M.Madheswaran - 'Experimental Study and steady state stability analysis of CLL-T Series Parallel Resonant Converter with Fuzzy controller using State Space Analysis'- *Iranian Journal of Electrical & Electronic Engineering*, Vol.8 (3), pp.259-267, September 2012.



15. C.Nagarajan and M.Madheswaran, "Analysis and Simulation of LCL Series Resonant Full Bridge Converter Using PWM Technique with Load Independent Operation" has been presented in ICTES'08, a IEEE / IET International Conference organized by M.G.R.University, Chennai.Vol.no.1, pp.190-195, Dec.2007
16. Suganthi Mullainathan, Ramesh Natarajan, "An SPSS and CNN modelling based quality assessment using ceramic materials and membrane filtration techniques", Revista Materia (Rio J.) Vol. 30, 2025, DOI: <https://doi.org/10.1590/1517-7076-RMAT-2024-0721>
17. M Suganthi, N Ramesh, "Treatment of water using natural zeolite as membrane filter", Journal of Environmental Protection and Ecology, Volume 23, Issue 2, pp: 520-530,2022
18. Vimal, V. R., John Justin Thangaraj, S., Narayanan, L. K., Alagu Thangam, S., Loganayagi, S., & Balakrishnan, S. (2025, April). Enhanced Phishing Detection and Classification Using an Ensemble Machine Learning Approach for URL Analysis. In International Conference on Information and Communication Technology for Intelligent Systems (pp. 229-239). Singapore: Springer Nature Singapore.
19. Binu, C. T., Kumar, S. S., Rubini, P., & Sudhakar, K. (2024). Enhancing Cloud Security through Machine Learning-Based Threat Prevention and Monitoring: The Development and Evaluation of the PBPM Framework. ResearchGate.
20. Murugeswari, B., Jayakumar, C., & Sarukesi, K. (2012). Secure Multi Party Computation Technique for Classification Rule Sharing. International Journal of Computer Applications, 55(7).